# TECHNICAL DATA CTOUCH Riva 65"

# LET'S GET SPECIFICIAN SPECIFICATION OF THE COLUMN TERM OF THE COLUMN T

Share, inspire, have fun!
With CTOUCH by your side.

**CTOUCH**<sup>®</sup>

# **CTOUCH**<sup>®</sup>

## **TECHNICAL DATA**

### **CTOUCH Riva 65"**

### **Product number**

■ CTOUCH Riva 65"

10052465

### **Touch system**

- Touch system: TrueBeam Touch
- Touch points: 32 on Windows, 20 on Android
- Touch tools: hands or other solid (soft tip) object
- Accuracy: ±1 mm
- Minimum response size: > 1,5 mm
- Touch resolution: 32.768 x 32.768 (pixels)
- Interface: USB 2.0 compatible (full speed) HID complaint,
   Plug & Play compatible. Backwards compatible with USB 1.1
- Supported OS: Windows, macOS, Chrome, Linux and Android
- Not required for 32 touch points (under Windows), macOS requires a driver for gestures.

### **Panel**

- Diagonal size: 64.53" (1.639 mm)
- Panel technology: TFT LCD
- Display resolution: 3.840 x 2.160
- Frame rate: 60 Hz
- Brightness: 400 cd/m²
- Aspect ratio: 16:9
- Contrast ratio (static): 5.000:1
- Contrast ratio (dynamic): 12.000:1
- Response time (gray to gray): 8 ms
- Display colours: 1.07 Billion (8 bits + FRC))
- Pixel pitch (W x H): 0.372 x 0.372 mm
- Viewing angle: 178° / 178°
- Backlight type: direct LED
- Service life: > 30.000 Hours
- Orientation: landscape

### Glass

- Glass: Triple S Glass (Smooth, Stripeless, Safety)
- Type: heat tempered, anti glare, safety glass
- Thickness: 4 mm
- Hardness: 7 Mohs

### **Connectivity**

- Video input (digital): 3x HDMI 2.0 (1x ARC), 1x DP 1.2, 1x USB-C (USB 3.1 Gen 2)
- Video output (digital): 1x HDMI out
- Video input (analog): 1x VGA (including 1x Mini Jack)
- Audio input: 1x Mini Jack (dedicated audio source)
- Audio output: 1x Mini Jack, 1x S/PDIF Optical
- USB: 3x USB 3.0 (type-A), 2x USB 2.0 (type A)
- Touch: 3x USB (type B)
- RS232C: 1x DE-9F
- LAN port: 2x RJ45 10/100/1000 BaseT
- Module-slots: 1x Wi-Fi slot, 1x OPS-slot (UHD@60Hz), 1x CTOUCH module-slot (modules are optional)
- Dedicated ports: 1x NFC Reader port, 1x Fingerprint Scanner port, 1x Human Presence Detection port (modules are optional)

### **Video**

- Eye comfort: blue light filter, eye protection mode
- Colour temperature: warm, cool, normal
- Picture modes: dynamic, standard, soft, user

### Sound: designed, tuned, built by HARMAN

- Transducers: 2 stereo JBL® 3-way speakers (tweeter, mid-range and woofer)
- Amplifier power: 80 watts
- Frequency range: 60 Hz 20 kHz
- Immersive JBL® back to front sound

### **COS**<sup>tm</sup>

- System version: Android 8.0
- Chipset: Hisilicon 811
- CPU: 2x ARM Cortex A73, 2x Cortex A53
- GPU: G51MP4
- Memory: 4 GB
- On-board storage: 32 GB

### **OSD**

 Languages: Danish, Dutch, English, Finnish, German, Hungarian, Norwegian, Spanish, Swedish

### power

- power supply: AC 100-240 V 50 / 60 Hz
- power consumption (in operation): 101 W
- power consumption (in standby): <= 0.5 W
- Energy Label: F
- Ambient light sensor

### **Quality approvals**

- Regulatory approvals: CE, FCC, RoHS compliant
- Green approval: WEEE
- ISO Standard: ISO9001 and ISO14001

### **Dimensions & Weight**

- Product dimensions (W x H x D): 1.503 x 892 x 103 mm
- Product weight: 46 kg
- Vesa mount (W x H): 400 x 600 mm, M8 Screw

### **Product accessories**

Accessories included: power cable (3 m), USB touch cable (3 m), HDMI cable (3 m), USB-C cable (1 m), remote control (incl. batteries), 2 passive pens, quick start guide & warranty card

### **Logistics information**

- Box size (W x H x D): 1.637 x 1.038 x 225 mm
- Gross weight: 56 kg
- EAN no.:

8719481480646

### Check out the CTOUCH Riva folder for more information.

All rights reserved. CTOUCH products and services mentioned herein as well as their respective logos are trademarks or registered trademarks of CTOUCH Europe B.V. All other product and service names mentioned are the trademarks of their respective owners. All weights and dimensions are approximate. Product specifications are subject to change without prior notification